

SAFETY DATA SHEET

1. Identification

Product identifier Oracle® Brick

Recommended use For Industrial Use Only.

Recommended restrictionsUsers should be informed of the potential presence of respirable dust and respirable crystalline silica as well as

their potential hazards. Appropriate training in the proper use and handling of this material should be provided as

required under applicable regulations.

Manufacturer/Supplier information

Company name: FRC Global

Address: 1000 N. West St.

Suite 1200 #3008 Wilmington, DE 19801

Product Support/Technical Services

Phone: (514) 931-5711

Website www.FRCglobal.com

Emergency telephone number: Corporate Office: (514) 931-5711

Technical Services: (514) 931-5711

Contact E-Mail: <u>LadleDr@FRCglobal.com</u>

2. Hazard(s) identification

Classified hazards This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves, protective clothing, and eye

protection. Dust may cause cancer.

Label elements This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and

MATERIAL NAME: ORACLE® BRICK

residues in accordance with local authority requirements. Wear protective gloves, protective clothing, and eye protection. Dust may cause cancer.

Hazard(s) not otherwise Classified (HNOC)

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves, protective clothing, and eye protection. Dust may cause cancer.

3. Composition/information on ingredients

•	•		
Chemical Name	Common Name/Synonyms	CAS Number	%
Magnesium Oxide		1309-48-4	*
Aluminum Oxide (Non-Fibrous)		1344-28-1	*
Graphite		7782-42-5	*
Phenol		108-95-2	*
Iron Oxide		1309-37-1	*
Formaldehyde		50-00-0	*
Other components below reportable levels			*

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove the victim to fresh air and keep at rest in a

position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use the mouth-to-mouth method if the victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Call a POISON CENTER or doctor/physician.

Skin contact Take off immediately all contaminated clothing. Wash with

plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

Eye contact Do not rub your eyes. Immediately flush your eyes with

plenty of water for at least 15 minutes. Remove contact lenses, if present, and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

MATERIAL NAME: ORACLE® BRICK

Ingestion Rinse mouth. Get medical advice/attention if you feel

unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat

symptomatically. Keep the victim warm. Keep the victim

under observation. Symptoms may be delayed.

General information Take off immediately all contaminated clothing. If

concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data

sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Use fire-extinguishing media appropriate for surrounding

materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not available.

Special protective equipment and precautions for firefighters

Not available.

Accidental release measures

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from, and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material if this is without risk. Cover with a plastic sheet to prevent spreading. Absorb in vermiculite, dry sand, or earth and place into containers.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into a waste container. Prevent product from entering drains. Following product recovery, flush the area with water.

MATERIAL NAME: ORACLE® BRICK

Small Spills: Sweep up or vacuum up spillage and collect it in a suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean the surface

thoroughly to remove residual contamination.

Never return spills to original containers for reuse. For

waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses, or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in the original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection Occupational exposure limits

US OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Phenol (CAS 108-95-2)	PEL	19 mg/m ³	Respirable dust.
Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	15 mg/m ³	Respirable fraction
Formaldehyde (CAS 50-00-0)	PEL	0.93 mg/m ³	Total dust.
Graphite (CAS 7782-42-5)	PEL	5 mg/m³ 15 mg/m³	Respirable fraction Total dust.
Iron Oxide (CAS 1309-37-1)	PEL	10 mg/m ³	Total dust.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m ³	Total particulate.

Type

Value

Form

MATERIAL NAME: ORACLE® BRICK

Components

Graphite (CAS 7782-42-5)	TWA	15 mppcf			
US ACGIH Threshold Limit Value	es				
Components	Туре	Value	Form		
Aluminum Oxide (Non-Fibrous (CAS 1344-28-1)	s) TWA	1 mg/m ³	Respirable fraction.		
Graphite (CAS 7782-42-5)	TWA	2 mg/m³	Respirable fraction.		
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m ³	Inhalable fraction.		
US NIOSH: Pocket Guide to Che	emical Hazaro	ds			
Components	Type	Value	Form		
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m ³	Respirable dust.		
_	No biologica ingredient(s)	l exposure limits w	ere noted for the		
	The resin binder in this product was specifically				
•	engineered to have low				
	toxicity, with minimal free-phenol (less than 100ppm in thi				
	refractory product) and no free-formaldehyde. Under				
		·	omposition products may		
		arbon monoxide, c	•		
	formaldehyde, phenol, and aromatic and/or aliphatic				
	compounds.	-,			
Appropriate engineering contro					
	Good genera	l ventilation (typic	ally 10 air changes per		
	hour) should	be used. Ventilation	on rates should be matche		
	to conditions	s. If applicable, use	process enclosures, local		
	exhaust vent	ilation, or other en	gineering controls to		
	maintain airb	orne levels below	recommended exposure		
	limits. If expo	osure limits have no	ot been established,		
	maintain airb	orne levels to an a	cceptable level. Eye wash		
	facilities and	an emergency sho	wer must be available		
		ng this product.			
	-		quipment hields (or goggles).		
Skin protection	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	viata chamical "as	istant gloves		
•		oriate chemical-resi	_		
			istant clothing. Use of an		
Dospiratory protoction	•	pron is recommend			
	Use a NIOSH/MSHA-approved respirator if there is a risk exposure to dust/fume at levels exceeding the exposure				
	exposure to	dust/ fulfile at levels	s exceeding the exposure		

limits.

MATERIAL NAME: ORACLE® BRICK

Thermal hazards Wear appropriate thermal protective clothing, when

necessary.

General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. Form Solid.

Color

Odor

Odor threshold

pH

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

Initial boiling point and boiling range

Not available.

Flash point

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.
Not available.

Vapor density

Relative density

Not available.

Not available.

Solubility(ies)

Vapor pressure

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal

conditions of use, storage, and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions

MATERIAL NAME: ORACLE® BRICK

No dangerous reaction is known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional. The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form before shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and, in that condition, the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to precured shapes.

Incompatible materials

Powerful oxidizers. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales

representative for clarification.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled.

Skin contact Dust or powder may irritate the skin.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical, and toxicological characteristics:

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Skin irritation. May cause redness and pain.

Information on toxicological effects

MATERIAL NAME: ORACLE® BRICK

Acute toxicity Toxic if inhaled. Toxic in contact with skin.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data is available to indicate product, or any

components present at greater than 0.1% are mutagenic or

genotoxic.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure

may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long-lasting effects.

Persistence and degradability No data is available on the degradability of this product.

Bio-accumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g., ozone

depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or

disposed of, is not hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste.

Hazardous waste code Not applicable.

Waste from residues / unused products

Not available.

Contaminated packaging Not available.

MATERIAL NAME: ORACLE® BRICK

14. Transport information

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes

Fire Hazard - No

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no) *
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

MATERIAL NAME: ORACLE® BRICK

United States Toxic Substances Control Act (TSCA) Inventory & Puerto Rico

No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respect to product liability, rests solely upon the purchaser thereof.

Prepared by: FRC Global November 2023

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided and believed to be correct as of the issue date. However, FRC Global makes no representation or warranties and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose before use. FRC Global will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or misuse of the information contained herein.

End of Safety Data Sheet

MATERIAL NAME: ORACLE® BRICK