

### SAFETY DATA SHEET

### 1. Identification

**Product identifier** FSG B Slide Gate Plates/Nozzles

**Recommended use** For Industrial Use Only

**Recommended restrictions** None Known.

#### Manufacturer/Supplier information

Company name: FRC Global

Address: 1000 N. West St.

Suite 1200 #3008

Wilmington, DE 19801

Product Support/Technical Services

Phone: (514) 931-5711

Website www.FRCglobal.com

Emergency telephone number: Corporate Office: (514) 931-5711

Technical Services: (514) 931-5711

Contact E-Mail: <u>LadleDr@FRCglobal.com</u>

### 2. Hazard(s) identification

Classified hazards This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. It may cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves, protective clothing, and eye

protection. Dust may cause cancer.

Label elements This item is defined as an article per OSHA (29 CFR

1910.1200) and is therefore exempt from labeling. A Safety

Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. It may cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves, protective clothing, and eye

protection. Dust may cause cancer.

Hazard(s) not otherwise classified (HNOC)

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. It may cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance

3. Composition/information on ingredients

5. 55				
Chemical Name	emical Name Common Name/Synonyms		%	
Magnesium Oxide		1309-48-4	*	
Phenol		108-95-2	*	
Iron Oxide		1309-37-1	*	
Formaldehyde		50-00-0	*	

<sup>\*</sup>Designates that a specific chemical identity and/or composition percentage has been withheld as a trade secret.

#### 4. First-aid measures

persist.

**Skin contact** Wash off with soap and water. Get medical attention if

irritation develops and persists.

**Eye contact** Do not rub your eyes. Rinse with water. Get medical

attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Dust may irritate the respiratory tract, skin, and eyes.

Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep the victim under observation.

Symptoms may be delayed.

General information If concerned: Get medical advice. Ensure that medical

personnel are aware of the material(s) involved and take

precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media Use fire-extinguishing media appropriate for surrounding

materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not available.

Special protective equipment and precautions for firefighters

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

Not available.

#### 6. Accidental release measures

#### Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from, and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA-approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

#### Methods and materials for containment and cleaning up

Stop the flow of material if this is without risk. Collect dust using a vacuum cleaner equipped with a HEPA filter. Large Spills: Wet down with water and dike for later disposal. Shovel the material into a waste container. Avoid the generation of dust during clean-up. Following product recovery, flush the area with water.

Small Spills: Sweep up or vacuum up spillage and collect it in a suitable container for disposal. For waste disposal, see Section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses, or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. It should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Keep away from incompatibles such as oxidizing agents and acids.

#### Conditions for safe storage, including any incompatibilities

Store locked up. Store in the original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Value Components Туре Form

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

Magnesium Oxide	PEL	15 mg/m³	Total particulate.			
(CAS 1309-48-4)						
US ACGIH Threshold Lin	nit Values					
Components	Туре	Value	Form			
Magnesium Oxide	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.			
(CAS 1309-48-4)						
Biological limit values		No biological exposure limits were noted for the ingredient(s).				
Exposure guidelines	The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol					
	(less tha	(less than 100ppm in this refractory product) and no free-				
	formalde	formaldehyde. Under certain conditions, thermal				

#### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and an emergency shower must be available when handling this product.

decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol, and

aromatic and/or aliphatic compounds.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Chemical respirator with organic vapor cartridge, full

facepiece, dust, and mist filter.

Skin protection

Hand protection

Other

Wear appropriate chemical-resistant gloves.

Use of an impervious apron is recommended.

**Respiratory protection** Use a NIOSH/MSHA-approved respirator if there is a risk of

exposure to dust/fume at levels exceeding the exposure

limits.

Thermal hazards Wear appropriate thermal protective clothing, when

necessary









#### **General Hygiene Considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

### 9. Physical and chemical properties

**Appearance** 

Physical state Solid. Form Solid.

Color

Odor

Odor threshold

pH

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

Initial boiling point and boiling range

Flash point Not available.
Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

**Solubility (water)** Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

# 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal

conditions of use, storage, and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction is known under conditions of

normal use.

**Conditions to avoid** Contact with incompatible materials. Refractories

containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional. The organic binder in this product falls into a class known

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form before shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and, in that condition, the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have decomposition characteristics similar to those of precured shapes.

Incompatible materials

Phosphorus. Chlorine. Powerful Oxidizers.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales

representative for clarification.

Hazardous decomposition products

No hazardous decomposition products are known.

### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Dust may irritate the respiratory system. Prolonged

inhalation may be harmful.

**Skin contact** Dust or powder may irritate the skin.

**Eye contact** Dust may irritate the eyes.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical, and toxicological characteristics:

Dust may irritate the respiratory tract, skin, and eyes.

Coughing.

Information on toxicological effects

Acute toxicity Not available.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with the eyes may cause temporary

irritation.

Respiratory or skin sensitization Respiratory sensitization

Not a respiratory sensitizer.

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data is available to indicate product, or any

components present at greater than 0.1% are mutagenic or

genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC,

ACGIH, NTP, or OSHA.

**Reproductive toxicity**This product is not expected to cause reproductive or

developmental effects.

**Developmental effects** This product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure

may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bio-accumulative potential

No data available. No data available.

Mobility in soil
Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential,

endocrine disruption, global warming potential) are

expected from this component.

# 13. Disposal considerations

**Disposal instructions**This product, in its present state, when discarded or

disposed of, is not hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste.

Hazardous waste code Not applicable.

Waste from residues / unused products

Not available.

**Contaminated packaging** Not available.

# 14. Transport information

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Chemical

Not listed.

SARA 313 (TRI reporting)

Not listed.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR

68.130) Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US Massachusetts RTK - Substance List

Magnesium Oxide (CAS 1309-48-4)

US New Jersey Worker and Community Right-to-Know Act

Magnesium Oxide (CAS 1309-48-4)

US Pennsylvania Worker and Community Right-to-Know Law

Magnesium Oxide (CAS 1309-48-4)

US Rhode Island RTK Not listed.

**US California Proposition 65** 

This product contains a chemical known to the State of

California to cause cancer.

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES

US California Proposition 65 - CRT: Listed date/Carcinogenic substance Formaldehyde (CAS 50-00-0) Listed: January 1, 1988

### 16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respect to product liability, rests solely upon the purchaser thereof.

Prepared by: FRC Global Date: October 2020

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided and believed to be correct as of the issue date. However, FRC Global makes no representation or warranties and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose before use. FRC Global will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or misuse of the information contained herein.

**End of Safety Data Sheet** 

MATERIAL NAME: FSGB SLIDE GATE PLATES/NOZZLES