

SAFETY DATA SHEET

1. Identification

Product identifier Magfill OLI-EBT 30%
Recommended use For Industrial Use Only

Recommended restrictions Users should be informed of the potential presence of

respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as

required under applicable regulations.

Manufacturer/Supplier information

Company name: FRC Global

Address: 1000 N. West St.

Suite 1200 #3008 Wilmington, DE 19801

Product Support/Technical Services

Phone: (514) 931-5711

Website www.FRCglobal.com

Emergency telephone number: Corporate Office: (514) 931-5711

Technical Services: (514) 931-5711

Contact E-Mail: <u>LadleDr@FRCglobal.com</u>

2. Hazard(s) identification

Physical hazardsNot classified.Heath hazardsCarcinogenicity

Environmental hazards OSHA-defined hazards

Label elements

Carcinogenicity Category 1A Not classified.



Not classified.

Signal word Danger.

Hazard Statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until

all safety precautions have been read and understood. Wear protective gloves, protective clothing, and eye

protection.

Response If concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/containers in accordance with local,

regional, national, and international regulations.

Hazard(s) not otherwise Classified (HNOC)

MATERIAL NAME: MAGFILL OLI-EBT 30%

None Known.

Supplemental information

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, a progressive and irreversible lung disease. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Chemical Name	Common Name/Synonyms	CAS Number	%
Magnesium Silicate			
MgO	Magnesium Oxide	1309-48-4	28-34
SiO ₂ **	Amorphous Silica	112926-00-8	26-32
SiO ₂	Quartz	1344-28-1	28-32
Fe ₂ O ₃	Iron (III) Oxide	1309-37-1	5-7
Al ₂ O ₃	Aluminum Oxide (Non-Fibrous)	1344-28-1	0.6-1.2
CaO	Calcium Oxide	1308-38-9	0.3-0.6
Others (K ₂ O, NAO)			1-1.3

^{**} Linked with magnesium in silicate form with less than 1 % free silica.

Common Name: Synthetic Olivine CAS Number: RN 12 44 003-26-6

Chemical name of impurities, solvents, and/or additives:

None

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or

persist.

Skin contact Wash off with soap and water. Get medical attention if

irritation develops and persists.

Eye contact Do not rub your eyes. Flush eyes immediately with water

for at least 15 minutes. Get medical attention if irritation

develops and persists.

Ingestion Unlikely route of exposure. If ingested in sufficient quantity

and the victim is conscious, give 1-2 glasses of water or milk. Never give anything by mouth to an unconscious person. Leave the decision to induce vomiting to qualified medical personnel, since particles may be aspirated into

the lungs. Seek immediate medical attention.

Most important symptoms/effects, acute and delayed

Dust may irritate the respiratory tract, skin, and eyes.

Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep the victim under observation.

Symptoms may be delayed.

MATERIAL NAME: MAGFILL OLI-EBT 30%

General information

If concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding

materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not available.

Special protective equipment and precautions for firefighters

Wet material should be kept out of eyes and off skin in any fire, and wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. The material does not give off toxic fumes in a fire unless it is molten.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA-approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material if this is without risk. Collect dust using a vacuum cleaner equipped with a HEPA filter. Large Spills: Wet down with water and dike for later disposal. Shovel the material into a waste container. Avoid the generation of dust during clean-up. Following product recovery, flush the area with water.

Small Spills: Sweep up or vacuum up spillage and collect it in a suitable container for disposal. For waste disposal, see Section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses, or onto the

ground.

7. Handling and storage Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid

MATERIAL NAME: MAGFILL OLI-EBT 30%

prolonged exposure. It should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in the original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Threshold limit values un	der regulation (S-2.1, r	1.15)	
Components	Type	Value	Form
Magfill		10 mg/m ³	Total dust.
		5 mg/m^3	Respirable fraction.

Occupational exposure limits

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	15 mg/m³ 5 mg/m³	Total Dust. Respirable fraction.
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m ³	
Iron Oxide Fume (CAS 1309-37-1)		10 mg/m ³	Total dust

US OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Quartz (SiO ₂)	TWA	0.3 mg/m ³	Total dust.
(CAS 14808-60-7)		0.1mg/m^3	Respirable.
		2.4 mppcf	Respirable.
Silicon Dioxide, Amorphous	TWA	0.8 mg/m ³	
(CAS 112926-00-8)		20 mppcf	

US ACGIH Threshold Limit Values

O / COM Thi Conord Emilie Values			
Components	Туре	Value	Form
Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m ³	Respirable fraction.
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m ³	

US NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
(CAS 14606-60-7)			

MATERIAL NAME: MAGFILL OLI-EBT 30%

Calcium Oxide (CAS 1305-78-8)

TWA

 2 mg/m^3

Biological limit values No biological exposure limits were noted for the

ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and

respirable) and respirable crystalline silica should be

monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the

Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation that may generate dust, use appropriate local exhaust ventilation to keep exposures below the

recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge, full

facepiece, dust and mist filter.

Skin protection

Hand protection

Other

Wear appropriate chemical-resistant gloves. Use of an impervious apron is recommended.

Respiratory protection Use a NIOSH/MSHA-approved respirator if there is a risk of

exposure to dust/fume at levels exceeding the exposure

limits.

Thermal hazards Wear appropriate thermal protective clothing, when

necessary.









General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

MATERIAL NAME: MAGFILL OLI-EBT 30%

Form Solid.

Color Varies from light to dark brown.

Odor No odor.
Odor threshold Not available.

pH 8.4
Melting point/freezing point <1700°C
Initial boiling point and boiling range

Not available.

Flash point

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure
Vapor density

Not available.
Not available.
88-92 lb./ ft³

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal

conditions of use, storage, and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction is known under conditions of

normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales

representative for clarification.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

MATERIAL NAME: MAGFILL OLI-EBT 30%

Information on likely routes of exposure

Inhalation Dust may irritate the respiratory system. Prolonged

inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical, and toxicological characteristics:

Dust may irritate the respiratory tract, skin, and eyes.

Coughing.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with the eyes may cause temporary

irritation.

Respiratory or skin sensitization Respiratory sensitization

Not a respiratory sensitizer.

Germ cell mutagenicity N

Skin sensitization This product is not expected to cause skin sensitization.

No data is available to indicate product, or any

components present at greater than 0.1% are mutagenic or

In 1997, IARC (the International Agency for Research on

genotoxic.

Carcinogenicity

Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However, in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust, and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry).

Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be

monitored and controlled.

MATERIAL NAME: MAGFILL OLI-EBT 30%

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (SiO₂) (CAS 14808-60-7) 1 Carcinogenic to humans.

US National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO₂) (CAS 14808-60-7) Known To Be Human Carcinogen.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or

developmental effects.

Developmental effects

Quartz (SiO₂) 0

Developmental effects - EU category

Quartz (SiO₂) 0

Embryotoxicity

Quartz (SiO₂) 0

Reproductively

Quartz (SiO₂) 0

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure

may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on

the environment.

Persistence and degradability

Bio-accumulative potential

Mobility in soil

No data is available on the degradability of this product.

No data available. No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone

depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or

disposed of, is not hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste

Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste

disposal partner or the responsible authority.

MATERIAL NAME: MAGFILL OLI-EBT 30%

Waste from residues / unused products

Not available.

Contaminated packaging Not available.

14. Transport information

DOT Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes

Fire Hazard - No

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Chemical

No.

SARA 313 (TRI reporting)

Chemical Name	CAS number	% by wt.		
Aluminum Oxide (Non-Fibrous)	1344-28-1	*		

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR

68.130) Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

MATERIAL NAME: MAGFILL OLI-EBT 30%

US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US Massachusetts RTK - Substance List

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Quartz (SiO₂) (CAS 14808-60-7) Calcium Oxide (CAS 1305-78-8)

US New Jersey Worker and Community Right-to-Know Act

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Quartz (SiO₂) (CAS 14808-60-7) Calcium Oxide (CAS 1305-78-8)

US Pennsylvania Worker and Community Right-to-Know Law

Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

Quartz (SiO₂) (CAS 14808-60-7) Calcium Oxide (CAS 1305-78-8)

US Rhode Island RTK Aluminum Oxide (Non-Fibrous) (CAS 1344-28-1)

US California Proposition 65

This product contains a chemical known to the State of

California to cause cancer.

US California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO₂) (CAS 14808-60-7) Listed: October 1, 1988

16. Other information, including date of preparation or last revision

This information is supplied to be informative and to alert the user of the material. The ultimate compliance with federal, state, and/or local regulations concerning the use of this material, or compliance with respect to product liability, rests solely upon the purchaser thereof.

Prepared by: FRC Global Date: May 2022

DISCLAIMER: Reasonable care has been taken in the preparation of the information provided, and believed to be correct as of the issue date. However, FRC Global makes no representation or warranties and assumes no responsibility as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purpose before use. FRC Global will not be responsible for any damages of any nature directly or indirectly whatsoever resulting from the use of, reliance upon, or misuse of the information contained herein.

End of Safety Data Sheet

MATERIAL NAME: MAGFILL OLI-EBT 30%